


No.3206LE MaX-LE Leading Edge Fall Protection Kit



No.TB3-6070 Tongue Buckle Harness



OSHA requires that SRL's anchored at or below a full body harness dorsal D-ring, are rated for leading edge Class 2. This would apply to roofers, roof loaders, framers, truss stackers, interior and exterior work, and leading edge hazard exposure. Any work performed where an overhead anchorage is not available.


ANSI Compliance

- SRL-LE Class 2: Z359.14-21
- 3 D-Ring Harness: Z359.11-14
- Hinge-2 Anchor: Z359.18 Type A

Contents

- SideWinder™ SRL-LE Class 2
- No.TB3-6070 Tongue buckle 3 D-ring harness
- No.3013-D Hinge-2™ anchor
- No.2084-3.5 10pc 3-1/2" WS screws
- No.2012-A 36pc 16d nail pack
- No.6420 All-Pakka™ cargo bag

Stainless Steel Brake System
Best for salt air environments



No.2084-3.5 Fastener Pack



10pc 3-1/2" WS Screws




No.3013-D Hinge-2™ Dacromet Coated



Adjustable Reuseable Anchor


Nail Pack 36pc Zinc Plated Duplex Nails



No.6420 Large All-Pakka™ Cargo Bag



English/Spanish Instruction Manual



MaX-LE Kit Specifications

Part No.	SRL	Harness	Size	Anchor	wt/lb
3206LE-30M	No.2903B-LE30	TB3-6070-HM	Medium	No.3013-D Hinge-2	20
3206LE-30L	30ft Length	TB3-6070-HL	Large		
3206LE-50M	No.2901B-LE50	TB3-6070-HM	Medium		29
3206LE-50L	50ft Length	TB3-6070-HL	Large		

Contact SAS sales team member for unit pricing.



Super Anchor Safety
Monroe, WA 98272, USA 425-488-8868