



A heavy duty tie-off lanyard specified for wrapping around steel or wood framed supporting structures. A thick wall clear PVC tubing sleeve protects the wire rope from abrasion and extends the service life.

User: 1 Person 310lb with tools and equipment

Min. Tensile Strength: 5,000lb

Mfg. SAS factory Monroe, WA USA

OSHA 1926.502/ANSI Z359.1

Part No.	Service Length
1332-3	3ft
1332-4	4ft
1332-5	5ft
1332-6	6ft
1332-X	Custom Length

- 2-1/4" ID
Galv. Ring

3/8"x7x19 Galv.
— Wire Rope
w/Galv.
Eye Thimble

– Alum. Swage
w/Clear PVC
Shrink Tube
Cover

PID/Inspection
Labels w/
Elastic Label
Keeper

- Clear Thick Wall PVC Tubing Sleeve

Wrap/Pass-Thru and Cinch Design

Wrap/Pass-Thru and Cinch Design

ry Swage

Alum. Swage

Clear PVC

Shrink Tube Cover

Alum. Swage

Clear PVC —
Shrink Tube Cover

Alum. Swage
— w/Clear PVC
Shrink Tube Cover

Galv.
— Eye
Thimble

— 2-1/8" OD
Zinc Plated Ring

B End

Primary

Inspection



 USA mfg. at
 Super Anchor Safety
 Monroe, WA 98272
 425-488-8868



Wire Rope Lanyard

Part No. _____ Length _____
1332
 DGM
 YOM _____

Wire Rope: Galv. 3/8"x7x19,
 14,400lb tensile strength
O-rings: Zinc plated 5,000lb min.
 tensile strength 3,600lb proof load
Swaggs: 3/8" oval aluminum
Max. User wt. 310lbs w/tools
 and equipment
Compliance:
 ANSI Z-359.1-07/OSHA 1926.502
 Use of a personal energy absorber is
 required if exposed to a free fall.

WARNING! Required to inspect
 before each use. Consult instruction
 manual shipped with this device at
 the time of purchase. Remove from
 service if subjected to a fall.

[illegible]